

TMG,

CT-40 Visit Phone Pair



Technical Specifications

CT-40

Faceplate: 16 Gauge, Beveled, Stainless Steel

Dimensions: 4 1/2" H x 4 1/2" W

Housing: Double-gang Mounting Box

Size: 4 1/2" H x 4 1/2" W x 2 1/4" D

Weight: 2 lbs. Each

No Voice Network required

Best Handset Available: Zenoy plastic handle is stronger than traditional Lexan type. Armored cord assembled with a steel lanyard providing 1200+ lbs. pull strength and a heavy 14 gauge steel retainer to prevent handset removal.

Power: Will operate on 24 to 48VDC phone line, system supplied power or min. 12VDC filtered power supply

Mounting: May be recessed or surface mounted

Relative Humidity: 0% to 95% condensing

Operating Temperature: -40 to 140 degrees Fahrenheit

Warranty: 2 Years

Replacement Parts

CT-10115-47 Security Screws (CT-40)

CT-40109-S 2 Wire 12" Carbon Handset

CT-20109-S 2 Wire 18" Carbon Handset

CT-60109-S 2 Wire 24" Carbon Handset

CT-10109-S 2 Wire 32" Carbon Handset

CT-30106 Invisible Hookswitch

CT-20205 12VDC Single Power Supply

Optional Equipment

TM-40: L-Shape Table Mount

CT-19195: Security Screwdriver (CT-40)

Ordering Options

CT-40+

SS = Stainless Steel

12 = 12" Mini Handset cord length

18 = 18" Short Handset cord length

24 = 24" Midsize Handset cord length

32 = 32" Standard Handset cord length

Repair and Refurbishment Services Available

Telcom Marketing Group, Inc. - 1380 Weber Industrial Drive - Cumming, GA 30041

Phone: 770.844.1346

Fax: 770.844.9079

Toll Free 877.844.1366

www.inmatetelephones.com