

TMG, Inc.

CT-40 & CT-210 Visit Phone "PIN" Pair



Technical Specifications

CT-40

Faceplate: 16 Gauge, Beveled, Stainless Steel

Dimensions: 4 1/2" H x 4 1/2" W

Housing: Double-gang Mounting Box

Size: 4 1/2" H x 4 1/2" W x 2 1/4" D

Weight: 2 lbs. Each

CT-210

Housing: 14 Gauge Stainless Steel

Size: 7 1/4" H x 5" W x 2 1/2" D

Weight: 5 lbs. Each

Connections: Spade Terminal and Modular

Replacement Parts

CT-10107 Chrome Cradle

CT-10115-47 Security Screws (CT-40)

CT-10115-06 Security Screw (CT-210)

CT-40109-M 12" Handset

CT-20109-M 18" Handset

CT-60109-M 24" Handset

CT-10109-M 32" Handset

CT-40109-S 2 Wire 12" Carbon Handset

CT-20109-S 2 Wire 18" Carbon Handset

CT-60109-S 2 Wire 24" Carbon Handset

CT-10109-S 2 Wire 32" Carbon Handset

CT-20106 Magnetic/Micro Hookswitch

CT-30106 Invisible Hookswitch

Optional Equipment

TM-50: L-Shape Table Mount

CT-19192: Security Screwdriver (CT-210)

CT-19195: Security Screwdriver (CT-40)

Handset: 12", 18", 24" or 32" armored cord with steel lanyard, and heavy 14 gauge steel retainer, over 1000 lbs. Pull strength

Power: Will operate on 24 to 48VDC phone line or system supplied power

Mounting: CT-210 will mount onto and cover an existing double-gang box. CT-40 may be recessed.

Relative Humidity: 0% to 95% condensing

Operating Temperature: -40 to 140 degrees Fahrenheit

Warranty: 2 Years

Ordering Options

CT-40+ & CT-210+

SS = Stainless Steel

12 = 12" Mini Handset cord length

18 = 18" Short Handset cord length

24 = 24" Midsize Handset cord length

32 = 32" Standard Handset cord length

MS = Magnetic/Micro Hookswitch

IHS = Invisible Hookswitch

Repair and Refurbishment Services Available

Telcom Marketing Group, Inc. - 1380 Weber Industrial Drive - Cumming, GA 30041

Phone: 770.844.1346

Fax: 770.844.9079

Toll Free 877.844.1366

www.inmatetelephones.com